

IP Outdoor Station

280SD-C3

Comparing with 902 Android intercom system, 280 Linux intercom system is more cost-effective. It offers multiple functions, including video intercom, door access, emergency call, security alarm, and property management, etc. It also supports communication with IP phone or SIP softphone, etc. via SIP protocol, and can be used with home automation and lift control system.



Specifications:

Physical Property	
System	Linux
CPU	1GHz , ARM Cortex-A7
SDRAM	128MB
Flash	64M DDR2
Product Size	116x192x47(mm)
Build-in Box size	100x177x45(mm)
Treppanning Size	105x182x52(mm)
Power	DC12V/POE
Standby power	1.5W
Rated Power	3W
RFID Card Reader	IC/ID (Optional), 20,000 pcs
Button	Mechanical Button
Temperature	-40°C - +70°C
Humidity	20%-93%
IP Class	IP55
Audio & Video	
Audio Codec	G.711
Video Codec	H.264
Camera	CMOS 1M pixel
LED Night Vision	Yes
Network	
Ethernet	10M/100Mbps, RJ-45
Protocol	TCP/IP, SIP
Interface	
Unlock circuit	Yes (Withstand max current 3.5A for lock)
Exit Button	Yes
RS485	Yes
Door Magnetic	Yes

Key features:

- Open the door by IC/ID card (20,000 users) or password (only one unlocking way is available)
- Elevator control
- Home automation
- Standard SIP 2.0
- PoE

Dimension & Installation:

